

Overview of microphones and capsules built by NEUMANN, Berlin

Neumann Type			Type	Year	Microphone Capsule				Amplifier					Remarks
					Type	Principle	Membrane	Year	Polar Pattern / Switchable Characteristics	Type of Pattern Switch	No. of Switches	Tube/ Semiconductor	Power Supply	
Neumann	Broadcast	Telefunken												
CM 3	M 1-2	—	microphone capsule	1927	CM 3	P	PVC/G	1927	O	—	—	—	—	capsule with thread, torpedo head for CMV 3
CMV 3	M 1-1	ElaMZ 027/1	microphone amplifier	1930	—	—	—	—	—	—	—	RE 084k	100 V 4 V	Neumann bottle, torpedo head
CM 5	M 1-2a	ElaMZ 026/2	microphone capsule	1930	CM 5	P	PVC/G	1930	O	—	—	—	—	capsule with thread, torpedo head for CMV 3
M 48	B-M 48	—	microphone capsule	1953	M 48 (KK 53)	P	Alu	1953	O	—	—	—	—	capsule with thread, torpedo head for CMV 3 + U 47 P
CMV 3a	M 1-1a	ElaMZ 028/1	microphone amplifier	1932	—	—	—	—	—	—	—	RE 084k	100 V 4 V	Neumann bottle bayonet
CM 8	M 7	ElaMZ 032/2	microphone capsule	1932	CM 8	PG	PVC/G	1932	C	—	—	—	—	for CMV 3a with bayonet
CM 7	M 8	ElaMZ 031/1	microphone capsule	1932	CM 7	PG	PVC/G	1932	8	—	—	—	—	for CMV 3a with bayonet
CM 9	M 9	—	microphone capsule	1932	CM 9	P	PVC/G	1932	O	—	—	—	—	for CMV 3a with bayonet
production for Siemens			Siemens capsule	1937 1942	Rel.mph 9 Rel.mph 19	P P	Alu Alu	1937 1942	O O	—	—	—	—	"rail capsule"
U 47	—	—	standard microphone	1949 -	M 7	PG	PVC/G	1932	O, C	S	1	VF 14	105 V	usable with CM 8 and CM 5 of CMV 3a
			standard microphone	-1965	K 49	PG	Pe/G	1960	O, C	S	1	VF 14	105 V	polyester membrane, screwed
U 47 N												Nuvis-tor 13CW4	105 V	successor for VF 14
U 47 P			standard microphone	1955	M 48	P	Alu	1953	O	—	—	VF 14	105 V	with torpedo head for capsule M 48

Overview of microphones and capsules built by NEUMANN, Berlin

Neumann Type			Type	Year	Microphone Capsule				Amplifier					Remarks
					Type	Principle	Membrane	Year	Polar Pattern / Switchable Characteristics	Type of Pattern Switch	No. of Switches	Tube/ Semiconductor	Power Supply	
Neumann	Broadcast	Telefunken												
MM 2	—	—	measur. microphone	1949 - 1954	MM 2	P	Alu	1949	O	—	—	VF 14	105 V	detached capsule, written calibration
M 49	—	—	standard microphone	1951 - 1974	M 7 K 49	PG PG	PVC/G Pe/G	1932 1960	O..C..8	ReP	—	MSC2 AC 701	120 V 4 V	amplifier developed with NWDR
M 50	—	—	standard microphone	1951 - 1971	KK 50 KK 53 KK 53 KK 83	P P P P	PVC/G Alu Ni Pe/G	1951 1954 1958 1965	O	—	—	MSC2 AC 701 AC 701	120 V 4 V	amplifier developed with NWDR
KM 53	M 153	—	miniature microphone	1953 - 1968	KK 53	P	Alu	1953	O, with Z 29 pad	—	—	AC 701	120 V 4 V	1st condenser microphone with 21 mm, developed with NWDR
KM 54	M 154	—	miniature microphone	1954 - 1969	KK 54	PG	Ni	1954	C, with Z 29	—	—	AC 701	120 V 4 V	
					KK 64...84	PG	Pe/G	64 on	pad	—	—			replacement for KK 54, capsule adapter
MM 3 (u)	—	—	measur. microphone	1954 - 1966	MM 3	P	Alu	1954	O	—	—	AC 701	120 V 4 V	detached capsule, written calibration
KM 56	M 156	—	miniature microphone	1955 - 1970	KK 56 later KK 88	PG	Ni	1955	O, C, 8 with Z 29/56 pad	S	1	AC 701	120 V 4 V	0,7 µm nickel membrane
U 48	—	—	standard microphone	1957 - 1965	see M 7 and K 49				C, 8	S	1	VF 14	105 V	see U 47
SM 2	—	—	stereo microphone	1957 - 1966	see KK 56...KK 88				O..C..8	Re (9)	2	AC 701	120 V 4 V	1st condenser stereo microphone
TM 53	—	—	microphone amplifier with capsule	1957 - 1958	TM 53	P	Alu	1957	O	—	—	AC 701	120 V 4 V	for Sennheiser, shotgun

Overview of microphones and capsules built by NEUMANN, Berlin

Neumann Type			Type	Year	Microphone Capsule				Amplifier					Remarks
					Type	Principle	Membrane	Year	Polar Pattern / Switchable Characteristics	Type of Pattern Switch	No. of Switches	Tube/ Semiconductor	Power Supply	
Neumann	Broadcast	Telefunken												
MM 5 (u)	—	—	measur. microphone	1959 - 1970	MM 5	P	Ni	1959	O	—	—	AC 701	120 V 4 V	see MM 2+MM 3, 1st measurement micr. w. calibration grid Z 68
KM 253	—	—	miniature microphone	1960 - 1967	see KK 53				O, with Z 29 Pad	—	—	AC 701	120 V 4 V	RF connectors
KM 254	—	—	miniature microphone	1960 - 1969	see KK 54				C, with Z 29 pad	—	—	AC 701	120 V 4 V	RF connectors
					see KK 64...KK 84				C, with Z 29 pad	—	—		120 V 4 V	replacement for KK 54
U 67	—	—	standard microphone	1960 - 1971	K 870/67	PG	Pe/G	1960	O, C, 8 -10 dB, LC	S	3	EF 86	210 V 6,3 V	
M 249	—	—	standard microphone	1961 - 1974	see K 49				O, C	ReP	—	AC 701	120 V 4 V	RF connectors
M 250	—	—	standard microphone	1961 - 1971	KK 53 KK 53 KK 83	P	Alu Ni Pe/G	1954 1958 1965	O	—	—	AC 701	120 V 4 V	RF connectors
KM 256	—	—	miniature microphone	1961 - 1970	see KK 56...KK 88				O, C, 8 with Z 29 pad	S	1	AC 701	120 V 4 V	RF connectors
SM 23	—	—	stereo microphone	1961 - 1966	see KK 56...KK 88				O, C, 8 with Z 29/SM2 pad	Re (9)	—	AC 701	120 V 4 V	separate supply for both amplifiers, double microphone
M 269	—	—	standard microphone	1962 - 1973	see K 870/67				O..C..8 -10 dB, LC	S/ReP	3	AC 701	120 V 4 V	U 67 for broadcast
SM 69	M 206	—	stereo microphone	1964 - 1973	see K 870/67				O..C..8	Re (9)	—	AC 701	120 V 4 V	
KM 63	—	—	miniature microphone	1964 - 1971	KK 63 later KK 83	P	Pe/G	1964	O	—	1	AC 701	120 V 4 V	amplifier fits KK 83, KK 84, KK 85
KM 64	M 164	—	miniature microphone	1964 - 1971	KK 64 later KK 84	PG	Pe/G	1964	C	—	1	AC 701	120 V 4 V	see KM 63

Overview of microphones and capsules built by NEUMANN, Berlin

Neumann Type			Type	Year	Microphone Capsule				Amplifier					Remarks
					Type	Principle	Membrane	Year	Polar Pattern / Switchable Characteristics	Type of Pattern Switch	No. of Switches	Tube/ Semiconductor	Power Supply	
Neumann	Broadcast	Telefunken												
KM 65	—	—	miniature microphone	1964 - 1971	KK 65 later KK 85	PG LC	Pe/G	1965	C LC	—	1	AC 701	120 V 4 V	see KM 63
U 64 (u)	—	—	miniature microphone	1964 - 1971	see KK 64...KK 84				C	—	—	7586 (ns)	120 V 5,5 V	Nuvistor, for USA, 1st microphone with XLR connector ('u' version)
SRM 64	—	—	stand tube microphone	1964 - 1971	see KK 64...KK 84				C	—	—	AC 701	120 V 4 V	detached capsule, with swivel
KM 64P	—	—	stand microphone	1965 - 1968	see KK 64...KK 84				C	—	—	—	120 V 4 V	detached capsule, with swivel
KTM	—	—	miniature microphone	1965 - 1966	see KK 64...KK 84				C	—	—	Fet	T 12	start of Fet 70 series, 24 mm, transformerless
KM 66	—	—	miniature microphone	1966 - 1969	see KK 64...KK 84				O, C, 8	S	1	AC 701	120 V 4 V	
KM 73	M 173	—	miniature microphone	1966 - 1970	see KK 63...KK 83				C	—	—	Fet	T 12	KM 63 with T 12
KM 74	M 174	—	miniature microphone	1966 - 1976	see KK 64...KK 84				C	—	—	Fet	T 12	successor of KTM, 21 mm
KM 75	—	—	miniature microphone	1966 - 1974	see KK 65...KK 85				C LC	—	—	Fet	T 12	KM 65 with T 12
KML	—	—	Lavallier microphone	1966 - 1975	see KK 65...KK 85				C	—	—	Fet	spec. + P48	
M 367	—	—	standard microphone	1966 - 1976	see K 870/67				O, C, 8 -10 dB, LC	S	3	AC 701	120 V 4 V	for France, with Sogie connectors
KM 83 (i) (mt)	—	—	miniature microphone	1966 - 1992	see KK 63...KK 83				O -10 dB	—	1	Fet	P48	KM 63, 64, 65 with P48, start of Fet 80 series,
KM 84 (i) (mt)	M 284	—	miniature microphone	1966 - 1992	see KK 64...KK 84				C -10 dB	—	1	Fet	P48	in „i“ and „mt“

Overview of microphones and capsules built by NEUMANN, Berlin

Neumann Type			Type	Year	Microphone Capsule				Amplifier					Remarks
					Type	Principle	Membrane	Year	Polar Pattern / Switchable Characteristics	Type of Pattern Switch	No. of Switches	Tube/ Semiconductor	Power Supply	
KM 85 (i) (mt)	—	—	miniature microphone	1966 - 1990	see KK 65...KK 85				C LC -10 dB	—	—	Fet	P48	amplifier fits KK 83, KK 84, KK 85
Neumann	Broad-cast	Telefunken												
U 87 (i) (mt)	—	—	standard microphone	1967 - 1986	K 87	PG	Pe/G	1967	O, C, 8 -10 dB, LC	S	3	Fet	P48	battery 2x 22,5 V, successor of U 67
KM 76	—	—	miniature microphone	1967 - 1976	see KK 64...KK 84				O, C, 8 -10 dB, LC	S	2	Fet	T 12	KM 66 with T 12
—	—	M 280K	miniature microphone	1968 - 1970	see KK 63...KK 83				O	—	—	Fet	P48	Made for Telefunken M 28. rear sound inlet
—	—	M 280N	miniature microphone	1968 - 1975	see KK 64...KK 84				C	—	—	Fet	P48	with sheet metal instead of gauze
KM 86 (i) (mt)	M 286	—	miniature microphone	1968 - 1986	see KK 84				O, C, 8 -10 dB	S	2	Fet	P48	KM 66 with P48
U 77			standard microphone	1968 - 1974	see K 870/67				O, C, 8 -10 dB, LC	S	3	Fet	T 12	battery 9 V
KMA, KMA-S7			clip microphone	1969 - 1985	KMA	P	Ni	1969	O	—	—	Fet	P48 indiv.	also with Beyer and Sennheiser wireless transmitters
KM 88 (i) (mt)			miniature microphone	1969 - 1986	see KK 56..KK 88				O, C, 8 -10 dB	S	2	Fet	P48	DC/DC converter
MK 24			measur. capsule	1969 - 1974	MK 24	P	NiFe	1969	O	—	—	Fet	200 V	1"-capsule for Hewlett-Packard
MK 12			measur. capsule	1970 - 1974	MK 12	P	NiFe	1970	O	—	—	Fet	200 V	see MK 24 ½" Permenorm membrane
SM 69 fet			stereo microphone	1970 - 2010	see K 870/67				O..C..8	Re (9)	—	Fet	P48 2x + spec.	special power supply NS 69, CU 48
U 397			standard microphone	1971 - 1976	see K 870/67				O..C..8 -10 dB, LC	S	3	Fet	-9 V	-9 V phantom power for France, transformerless
SRM 83			stand tube microphone	1971 - 1990	see KK 83				O	—	—	Fet	P48	
SRM 84			stand tube microphone	1971 - 1990	see KK 84				C	—	—	Fet	P48	see SRM 63/64/65

Overview of microphones and capsules built by NEUMANN, Berlin

Neumann Type			Type	Year	Microphone Capsule				Amplifier					Remarks	
					Type	Principle	Membrane	Year	Polar Pattern / Switchable Characteristics	Type of Pattern Switch	No. of Switches	Tube/ Semi-conductor	Power Supply		
SRM 85	stand tube microphone	1971 - 1990	see KK 85							C LC	—	—	Fet	P48	
KMS 85 (i) (mt)	vocal microphone	1971 - 1985	see KK 84							C	—	—	Fet	P48	pop and shock protected
U 47 fet (i) (mt)	standard microphone	1972 - 1986	K 47	PG	Pe/G	1972			C -10 dB, LC, -6 dB	—	3	Fet	P48	successor of U 47	
KU 80 (i) mt	dummy head	1973 - 1981	see KK 83							Ear -10 dB	—	1	Fet	P48 2 x	for head-related stereo recordings
QM 69	quadro microphone	1974 - 1985	see K 870/67							4 x C	—	—	Fet	P48 4 x	4 x cardioid 4 x amplifier
U 497	standard microphone	1975 - 1985	see K 49							O, C, 8 -10 dB, LC	S	3	Fet	P12	for France DC/DC converter
KMS 84 (i) (mt)	vocal microphone	1977 - 1991	see KK 84							C -10 dB, LC	—	2	Fet	P48	successor of KMS 85, removable grille, colours
KMR 82 (i) (mt)	shotgun microphone	1978 -	KK 82	PG Interfer	Pe/G	1978			Lobe LC, H	—	2	Fet	P48		
USM 69 (i) (mt)	stereo microphone	1979 -	see K 870/67							O, BC, C, HC, 8	S	2	Fet	P48 2 x	DC/DC converter
U 89 (i) (mt)	standard microphone	1980 -	K 89	PG	Pe/G	1979			O, BC, C, HC, 8 -6 dB, LC	S	3	Fet	P48	DC/DC converter	
KMF 4 i, mt	miniature microphone	1982 - 1988	KK 4	PG	Pe/G	1982			C -10 dB, LC	—	2	Fet	P48	"mt" only, detached capsule, 17 mm	
KU 81 i	dummy head	1982 - 1992	see KK 83							Ear -10 dB, LC	—	2	Fet	P48 2 x	see KU 80, diffuse field equalized
KMR 81 (i) (mt)	shotgun microphone	1983 -	KK 81	PG Interfer	Pe/G	1982			Lobe -10 dB, LC	—	2	Fet	P48	AES 1982	
TLM 170 i (mt)	standard microphone	1983 - 1993	see K 89							O, BC, C, HC, 8, Re -10 dB, LC	S	3	Fet	P48 P24	DC/DC patent, transformerless
TLM 170 i ni polished Gotham Audio Jubilee	standard microphone	1983	see K 89							O, BC, C, HC, 8, Re -10 dB, LC	S	3	Fet	P48 P24	Limited Edition 100 pcs.

Overview of microphones and capsules built by NEUMANN, Berlin

Neumann Type			Type	Year	Microphone Capsule				Amplifier					Remarks
					Type	Principle	Membrane	Year	Polar Pattern / Switchable Characteristics	Type of Pattern Switch	No. of Switches	Tube/ Semi-conductor	Power Supply	
U 87 Ai (mt)			standard microphone	1986-	see K 870/67				O, C, 8 -10 dB, LC	S	3	Fet	P48	DC/DC instead of batteries
RSM 190 system			stereo shotgun microphone	1987	KK 190MS	PG Interfer	Pe/G	1987	Lobe, 8 MTX	Re (6)	2	Fet	P48 2 x	MS-microphone with matrix box MS, XY Figure-8 level control, „mt“ only
RSM 191 (A) system			stereo shotgun microphone	1988 - 2013	KK 190MS	PG Interfer	Pe/G	1987	Lobe, 8 MTX	Re (6)	3 (4)	Fet	P48 2 x	see RSM 190, matrix with -L,-R settings, T, -10 dB, battery 9 V
KM 100 system			variable miniature microphone system	1988 - 2015	AK 30 AK 31 AK 40 AK 43 AK 45 AK 50	P P PG PG PG LC PG	Pe/G	1988	O O C BC C HC -10 dB	—	1	Fet	P48	exchangeable active capsules with KM 100 output stage
GFM 132			boundary layer microphone	1990 - 2012	K 32	P	Pe/G	1990	HS -10 dB	—	1	Fet	P48	even in free and diffuse field
TLM 50			pressure microphone	1990 - 2014	K 33 K 33 Ti	P	Ni Ti	1990 2001	O -10 dB, LC	—	2	Fet	P48	capsule in sphere 40 mm
KMS 140 KMS 150			vocal microphone	1991 - 2012	see AK 40 see AK 50				C HC -10 dB, LC	—	2	Fet	P48	pop and shock protected
TLM 171			standard microphone	1992	see K 87				O, BC, C, HC, 8 -10 dB, LC	S	3	Fet	P48	limited edition
KU 100			dummy head	1992 -	see 2 x KK 83				Ear -10 dB, LC	—	3	Fet	P48, batt., extern	for head-related stereo recordings
KFM 100			sphere microphone	1992 - 1997	see 2 x K 32				O	—	—	Fet	P48 2 x	stereo main microphone
U 67			standard microphone	1993	see K 67				O, C, 8 -10 dB, LC	S	3	EF 86	210 V 6,3 V	reissue, limited edition

Overview of microphones and capsules built by NEUMANN, Berlin

Neumann Type			Type	Year	Microphone Capsule				Amplifier					Remarks
					Type	Principle	Membrane	Year	Polar Pattern / Switchable Characteristics	Type of Pattern Switch	No. of Switches	Tube/ Semiconductor	Power Supply	
TLM 193 (ni)			standard microphone	1993 -	see K 89				C	—	—	Fet	P48	with SG 193, (special edition in nickel)
TLM 170 R			standard microphone	1993 -	see K 89				O, BC, C, HC, 8, Re -10 dB, LC	S/Re (5)	3	Fet	P48	remote pattern switch (patented) with N 48 R-2 power supply
KM 184			miniature microphone	1993 -	K 40	PG	Pe/G	1988	C	—	—	Fet	P48	capsule of AK 40 / KM 100 system
M 149 Tube			standard microphone	1995 -	see K 49				9fold: O...C...8 7fold: LC	S	2	6111 WA	N 149 32/5,2V	set with KT 8 cable, N 149 power supply and EA 170
KM 84 A			miniature microphone	1996	see KK 64...KK 84				C	—	—	Fet	P48	special edition for NHK, Japan
KM 120			miniature microphone	1997 -	K 20	PG	Pe/G	1997	8	—	—	Fet	P48	capsule AK 20 for KM 100 system
TLM 103			standard microphone	1997 -	K 103	PG	Pe/G	1997	C	—	—	Fet	P48	with SG 1
U 87 Gold			standard microphone	1998	see K 870/67				O, C, 8 -10 dB, LC	S	3	Fet	P48	limited edition, 70 years Neumann
M 147 Tube			standard microphone	1998 -	see K 47				C	—	—	6111 WA	N149 A 32/5,2V	set with KT 8 cable, N 149 A power supply and SG 1
KM 183			miniature microphone	1999 -	K 30	P	Pe/G	1988	O	—	—	Fet	P48	capsule of AK 30 / KM 100 system
KM 185			miniature microphone	1999 -	K 50	PG	Pe/G	1988	HC	—	—	Fet	P48	capsule of AK 50 / KM 100 system
KMS 105			vocal microphone	1999 -	K 105	PG	Pe/G	1988	SC	—	—	Fet	P48	pop and shock protected
M 150 Tube			standard microphone	2000 -	K 33	P	Ti	1990	K -10 dB, T	—	2	6111 WA	N149 A 32/5,2V	capsule in 40 mm sphere, with KT 8 cable, N 149 A/V power supply and EA 170
KK 105 S			capsule head	2002-	K 105	PG	Pe/G	1988	SC	—	—	Fet	—	for Sennheiser SKM 5000/ 5200 (N) transmitter

Overview of microphones and capsules built by NEUMANN, Berlin

Neumann Type			Type	Year	Microphone Capsule				Amplifier					Remarks
					Type	Principle	Membrane	Year	Polar Pattern / Switchable Characteristics	Type of Pattern Switch	No. of Switches	Tube/ Semiconductor	Power Supply	
TLM 127			standard microphone	2003 - 2008	K 127	PG	Pe/G	2003	O, C, Re -14 dB, LC	S/Re (5)	3	Fet	P48	remote pattern control (patent) with N 48 R-2 & N 248 ps
D-01 Solution-D			standard microphone with digital interface	2003 -	K 07	PG	Pe/G	2001	O ... C ... 8 -6 /-12/-18 dB LC, compr./limiter & much more	Re (15)	—	Fet	AES42	system with DMI interface and RCS software
BCM 104			broadcast microphone	2003 -	K 04	PG	Pe/G	2003	C, -14 dB, LC	—	2 (int.)	Fet	P48	fixture with structure born noise decoupling & pop filter included
KK 104 S			capsule head	2004 -	K 104	PG	Pe/G	1988	C	—	—	Fet	—	for Sennheiser SKM 5000/5200 (N) transmitter
BCM 705			broadcast microphone	2005 -	KD 705 dyn.	PG	PETP	2005	SC	—	—	—	—	fixture with structure born noise decoupling & pop filter included
KMS 104			vocal microphone	2006 -	K 104	PG	Pe/G	1988	C	—	—	Fet	P48	pop and shock protected
TLM 49			standard microphone	2006 -	K 47	PG	Pe/G	1969	C	—	—	Fet	P48	
KM D Solution-D			miniature microphone with digital interface	2006 - 2009 -	KK 183 KK 184 KK 185 KK 131 KK 143 KK 145 KK 120 KK 133	P PG PG P PG PG PG P	Pe/G Ti	2006 2009	O, C, 8, SC, WC -6 /-12/-18 dB LC, compr./limiter & much more	—	—	Fet	AES42	extensive accessories, e.g. to use capsules separated from the output stage; with different configurations available
U 87 Anniversary			standard microphone	2007 -	see K 870/67				O, C, 8 -10 dB, LC	S	3	Fet	P48	Special edition celebrating 40 years of U87. Special case, finish + pop filter

Overview of microphones and capsules built by NEUMANN, Berlin

Neumann Type			Type	Year	Microphone Capsule				Amplifier					Remarks
					Type	Principle	Membrane	Year	Polar Pattern / Switchable Characteristics	Type of Pattern Switch	No. of Switches	Tube/ Semiconductor	Power Supply	
TLM 103 D	standard microphone with digital interface	2008 -	K 103	PG	Pe/G	1997	C -6 /-12/-18 dB LC, compr./limiter & much more	—	—	Fet	AES42	digital version of the TLM 103 microphone		
TLM 67	standard microphone	2008 -	K 870/67	PG	Pe/G	1960	O, C, 8 -10 dB, LC	S	3	Fet	P48			
TLM 102	standard microphone	2009 -	K 102	PG	Pe/G	2009	C	—	—	Fet	P48			
KMS 104 plus	vocal microphone	2009 -	K 104	PG	Pe/G	1988	C	—	—	Fet	P48	like KMS 104 but with more extended bass frequency response		
KM A	miniature microphone series	2006 - 2009-	KK 183 KK 184 KK 185 KK 131 KK 143 KK 145 KK 120 KK 133	P PG PG P PG PG PG P	Pe/G Ti	2006 2009	O, C, 8, SC, WC -10 dB	—	1	Fet	P48	extensive accessories, e.g. to use capsules separated from the output stage; with different configurations available		
KMS 104 D	vocal microphone	2010 -	K 104	PG	Pe/G	1988	C -6 /-12/-18 dB LC, compr./limiter & much more	—	—	Fet	AES42	digital version of the KMS 104 microphone		
KMS 105 D	vocal microphone	2010 -	K 105	PG	Pe/G	1988	SC -6 /-12/-18 dB LC, compr./limiter & much more	—	—	Fet	AES42	digital version of the KMS 105 microphone		
KMR 81 D	shotgun microphone	2010 -	KK 81	PG Interfer	Pe/G	1982	SC/Lobe -6 /-12/-18 dB LC, compr./limiter & much more	—	—	Fet	AES42	digital version of the KMR 81 microphone		
KK 204	capsule head	2012-	K 104	PG	Pe/G	1988	C	—	—	Fet	—	for Sennheiser SKM 2000, 6000, 9000		

Overview of microphones and capsules built by NEUMANN, Berlin

Neumann Type			Type	Year	Microphone Capsule				Amplifier					Remarks
					Type	Principle	Membrane	Year	Polar Pattern / Switchable Characteristics	Type of Pattern Switch	No. of Switches	Tube/ Semiconductor	Power Supply	
KK 205			capsule head	2012 -	K 105	PG	Pe/G	1988	SC	—	—	Fet	—	for Sennheiser SKM 2000, 6000, 9000
TLM 107			standard microphone	2014 -	K 107	PG	Pe/G	2014	O, WC, C, SC,8 -6 /-12 dB LC 40 Hz, 100 Hz	S	1	Fet	P48	navigation switch
U 47 fet i			standard microphone	2014 -	see K 47				N -10 dB, T, -6 dB	—	3	Fet	P48	Reissue
U 87 Rhodium			standard microphone	2017 - 2018	see K 870 / 67				K, N, A -10 dB, T	U	3	Fet	P48	Special edition celebrating 50 years of U 87
U 67			standard microphone	2018 -	see K 870 / 67				K, N, A -10 dB, T	U	3	EF 86	210 V 6,3 V	Reissue

Overview of microphones and capsules built by NEUMANN, Berlin

Abbreviations

8	figure-8, bidirectional	P	pressure transducer
Alu	aluminium	P 12	phantom power 12 V
C	cardioid	P 24	phantom power 24 V (IEC 61938)
DC/DC	DC/DC converter in microphone	P 48	phantom power 48 V (IEC 61938)
dyn	dynamic capsule	Pe/G	polyester, gold sputtered
H	high cut	PETP	Polyethylenterephthalat
HC	hypercardioid	PG	pressure gradient transducer
HS	hemisphere	PVC/G	PVC, gold sputtered
i	XLR connectors	Re	remote control
(i)	with XLR or DIN connectors	Re (6)	remote pattern switching, 6 settings
interfer	interference principle	Re (9)	remote pattern switching, 9 settings
LC	low cut	ReP	remote pattern control with potentiometer
MS	mid-side intensity stereophony	SC	supercardioid
mt	black matte	T 12	AB-power (Tonader) 12 V DIN 45595
(mt)	black matte oder nickel matte	Ti	titanium
Ni	nickel	U (u)	mechanically/electrically switchable at the microphone
NiFe	nickel/iron	WC	wide cardioid
ns	Nuvistor	XY	left-right intensity stereophony
O	omnidirectional	Z	accessories
Op	OpAmp		